



PLASMA CUTTING

EASYCUT K	101
EASYCUT	102
CUTTER	103





EASYCUT K



PLASMA

COMPRESSOR INSIDE • 1~

Plasma torch
TPT 25, 4m
068087


Plasma torch
TPT 35, 4m
080775



EASYCUT K25

230 V • 1 ~ 25 A Fe 8 mm
Al/CrNi 6 mm

P400 COMPRESSOR




TPT 25, 4 m 068087 2 m, 10 mm²
068063



Youtube

COMPRESSOR COMPRESSOR
INSIDE



Youtube

ULTRA
LIGHT &
COMPACT



INTEGRATED
AIR FILTER
+
AUTOMATIC
DRAIN


PFC
EN 61000-3-12
POWER FACTOR
CORRECTION



EASYCUT K35 PFC

230 V • 1 ~ 35 A Fe 15 mm
Al/CrNi 10 mm

P400 PFC AD COMPRESSOR



TPT35, 4 m 080775 2 m, 10 mm²
080768





TPT35, 4 m 2 m, 10 mm² Box TPT35 080782 UNIVERSAL 800 051331
080805

OPTIONS

Consumables

					Boxes - Coffrets
for TPT25	x4 040236	x10 040212	x2 040175	x10 040168	039971
	x1	x1	x1	x1	
for TPT35	x4 040182	x10 080799	x2 040175	x10 040168	080782
	x1	x1	x1	x1	

Compas
040205



PLASMA 600
040298
↓ 39 x 58 x 62 cm / 8.2 kg
⊗ 63 x 30 x 11 cm / 8.8 kg



Universal 800
051331
↓ 48 x 62 x 81 cm / 17.6 kg
⊗ 81 x 52 x 15 cm / 18.1 kg

 MADE IN FRANCE EN60974-1			I ₂	 mm				INTEGRATED TECHNOLOGY					AIR SYSTEM			EN 60974-1 (40°C)				 Protected & compatible power generator (+/-15%)	
				Coupe max Severance cut		Coupe propre Clean cut															
				Fe	Al/GrNi	Fe	Al/GrNi	P400	PFC	AD	IP23	COMPRESSOR	min	ideal	max	I 60%	X% I2 max	100%			LxWxH cm / kg
EASYCUT K25	230V 1~	16	10 → 25	8	6	6	4	■	—	—	—	■	included			15 A	35%	—	53 x 31 x 48 / 19	6.5 kW	7.5 kVA
EASYCUT K35 PFC	230V 1~	16	10 → 35	15	10	10	8	■	■	■	■	■	included			26 A	30%	—	45 x 26 x 36 / 27	8 kW	10 kVA



EASYCUT / CUTTER

PLASMA

1~




Youtube



Plasma torch
TPT 25, 4m
068087

Plasma torch
TPT 35, 4m
080775

Plasma torch
TPT 40, 4m
060753



INCLUDED :
8 mm

DIGITAL
PRESSURE SENSOR




IDEAL
CARBODY REPAIR



EASYCUT 25

230 V • 1 ~	25 A	Fe 8 mm Al/CrNi 6 mm
-------------	------	-------------------------



TPT 25, 4 m 068087 2 m, 10 mm²


065543
072046



EASYCUT 30 FV

110 → 230 V • 1 ~	30 A	Fe 15 mm Al/CrNi 10 mm
-------------------	------	---------------------------

P400 PFC FV



TPT 40, 4 m 060753 2 m, 10 mm²


013858

OPTIONS

COMPAS
for TPT 40, TPT 25, TPT 35,
MT 25K / MT 35K
x1
040199



040205




Consumables

	MT25K	TPT25	MT35K	TPT35	TPT40
	x4 040182	x4 040236	x4 040229	x4 040182	x4 040236
	x10 040151	x10 040212	x10 040212	x10 080799	x10 040212
	x2 040175	x2 040175	x2 040175	x2 040175	x2 040175
	x10 040168	x10 040168	x10 040168	x10 040168	x10 040168
Boxes - Coffrets	039971	070721	039964	080782	039957

Trolley - Chariot


PLASMA 600 040298	Universal 800 051331	Jobsite XL 039568
39 x 58 x 62 cm / 8.2 kg	48 x 62 x 81 cm / 17.6 kg	60 x 59 x 115 cm / 18.4 kg
63 x 30 x 11 cm / 8.8 kg	81 x 52 x 15 cm / 18.1 kg	66 x 47 x 20 cm / 19.6 kg

Compressed air cleaning
filter for Plasma Cutter 40
- Filtre déshumificateur
spécial Plasma
039728




Filter
cartridge
- Cartouche
pour filtre
039735


AD ANTI-DUST VENTILATION CORRIDOR




PFC + FV POWER FACTOR CORRECTION + FLEXIBLE VOLTAGE




CNC COMPUTER NUMERICAL CONTROL



DIGITAL (PRESSURE SENSOR)



DIGITAL (PRESSURE SENSOR)




Youtube



EASYCUT 40

230 V • 1 ~ 40 A

Fe 18 mm
Al/CrNi 15 mm



TPT 40, 4 m 060753 2 m, 10 mm²

029743

CUTTER 45 CT

110 → 230 V • 1 ~ 45 A


Fe 30 mm
Al/CrNi 20 mm

P400 PFC FV GRID CUT AD IP 23 CNC ANALOGIC



2 m, 10 mm²

014787



TPT 40, 4 m 2 m, 10 mm²

013629



MT 70, 6 m

062962

Box 20-50A 061613

 CE NORM. EN 60974-1					 mm						INTEGRATED TECHNOLOGY							AIR SYSTEM			EN 60974-1 (40°C)				 Protected & compatible power generator (+/-15%)		
					Coupe max Severance cut			Coupe propre Clean cut			Percage Piercing	P400	PFC	FV	GRID CUT	AD	IP23	CNC	min	ideal	max	I 60%	X% I2 max			100%	LxWxH cm / kg
					Fe	Al/CrNi		Fe	Al/CrNi		Fe																
50/60 Hz			A	A	Fe	Al/CrNi	Fe	Al/CrNi	Fe	Al/CrNi																	
MADE IN GYS CHINA	EASYCUT 25		230V 1~	16	10 → 25	8	6	6	4	—	—	—	—	—	—	—	2.5 bar	4.5 bar 115 L/min	6.5 bar	15 A	30%	10A	45 x 25 x 35 / 9.7	—	—		
			230V 1~ 110V 1~	16 32	10 → 30 10 → 30	15	10	10	8	—	—	■	■	■	—	—	—	—	2.5 bar 5 bar 115 L/min	9 bar	23 A 19 A	30% 25%	20 A 15 A	51 x 29 x 37 / 14.3	6.5 kW	6 kVA	
MADE IN GYS CHINA	EASYCUT 40		230V 1~	16	10 → 40	20	15	15	10	—	—	—	—	—	—	—	2.5 bar	4.5 bar 115 L/min	6.5 bar	10 A	20%	—	45 x 25 x 35 / 11.5	—	—		
MADE IN FRANCE	CUTTER 45CT	TPT 40	230V 1~	16	15 → 45	20	15	15	10	8	6	■	■	■	■	■	■	5 bar	5.2 bar 115 L/min	7 bar	41 A	50%	32 A	51 x 31 x 47 / 16.4	10.5 kW	8 kVA	
			110V 1~	32	15 → 30	15	10	10	8	—	—										—	—	—				—
		MT 70	230V 1~	32	15 → 45	30	20	25	15	12	10	—	—	—	—	—	—	—	5 bar	5.2 bar 185 L/min	7 bar	41 A	50%				32 A
			110V 1~	32	15 → 30	15	10	10	8	—	—											—	—				—

